



4K2K Plasma Display

TH-152UX1 TENTATIVE

● Product specification (design and specification subject to change without notice)

■ DISPLAY PANEL

Screen Size(Diagonal)	152.0-inch
Aspect ratio	17:9
Effective Display Area(W x H)	3,416 x 1,801 mm (134.5" x 70.9")
Number of pixels (H x V)	4,096 x 2,160 pixels
Pixel pitch(H x V)	0.834 x 0.834 mm (0.0328" x 0.0328")
Full HD 3D	Yes*1

*1: An optional External IR Emitter is required for viewing 3D images.

■ CONNECTION TERMINAL

HD-SDI INPUT*2	HD-SDI(Dual-Link) x 4
DVI INPUT*2	DVI (Single-Link) x 4
RGB INPUT	D-SUB15P x 1
HDMI INPUT	HDMI x 2
Function Slot : SLOT 2.0	DVI-D x 1 (Audio Input is not available.)

*3D input is only for the HDMI terminal.

*2: 4 inputs is set and only for one 4K signal. You can not input 4 different signal to each inputs.

■ CONTROL TERMINAL

SERIAL	D-SUB 9PIN x 1 (EXTERNAL CONTROL TERMINAL), RS-232C COMPATIBLE
External IR emitter control terminal	M3 Jack x 1 (for 3D active shutter eyewear)

■ ELECTRICAL

Power Requirements	AC200~240V 50/60Hz
Power Consumption	approx. 4,500W

■ MECHANICAL

Dimemions (W x H x D)	3,600 × 1,980 × 147*3 mm (141.8" x 78.0" x 5.8"*3)
Weight	approx. 590 kg (1300.7 lbs.)

*3: Exclusive of portion (10.3"[260 mm] when including the protruding portion of the slot)

■ OPTIONAL ACCESSORIES

Pedestal	TY-ST152UX1
Wall-hanging bracket	TY-WK152UX1
HD-SDI Terminal Board	TY-FB9HD
Dual Link HD-SDI Terminal Board	TY-FB11DHD
DVI-D Terminal Board	TY-FB11DD
IR Emitter	(TBD)
3D Eyewear	TY-EW3D10

*The terminal boards accept only 2D signals.

Cautions: This drawing is not a scale
Units : inches (mm)

● DIMENSIONS

